

深圳上线科技有限公司	Doc.No.:
REV: A	PAGE: 1/17
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE: 2023-09-22

Specifications

TFT-LCDmodule

Model No: MD024-QVGA-01-V01

For Customer's Acceptance	
Approved by	Comment

	Signature	Date
Prepared by		
Checked by		
Approved by		

深圳上线科技有限公司	Doc.No.:	
	REV: A	PAGE: 2/17
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE: 2023-09-22	

Contents

1	General Description	3
1.1	Features	3
1.2	Application	3
2	Outline Dimension	3
3	Module specification of the module	4
4	Electrical Characteristics	5
4.1	TFT-LCD Module	5
4.2	Back-Light Unit	6
5	TFT-LCM Interface Specification	7
6	Timing Characteristics	7
7	Optical Specification	9
8	Environment Absolute Maximum Ratings	12
9	Reliability Test Items	12
10	Inspection Standard	13
11	Package	14
12	Precautions	15
12.1	Handling	15
12.2	Storage	15
12.3	Operation	16
12.4	Touch Panel Mounting Notes	16
12.5	Others	17
13	Records of Version	17

1 General Description

MD024-QVGA-01-V01 is a transmissive type a-Si TFT-LCD (amorphous silicon thin film transistor liquid crystal display) module, which is composed of a TFT-LCD panel, a driver circuit a backlight unit, The panel size is 2.4inch and thresolution is 240x320. High image quality a-Si TFT LCD module. Partial-screen display function is available. Sleep and Stand-by modes are available for power saving.

1.1 Features

No	Item	Specification	Remark
1	Display Mode	High Resolution & Wide View	
2	Screen Size	2.4inch (diagonal)	
3	Resolution	240XRGBX320	
4	Color Number	262K TFT	
5	Color Arrangement	RGB-stripe	
6	Driver IC	ST7789V	
7	Back Light	White LED*4	
8	Viewing Direction	ALL	
9	Interface	MCU Parallel/RGB	
10	Surface Treatment	UV Cut	
11	Module brightness	300 cd/m ²	

1.2 Application


- ◆ Mobile phone.
- ◆ Portable multimedia device.

2 Outline Dimension

The mechanical detail is shown in Fig. 1 and summarized in Table 1 below.

Parameter	Specifications	Unit
Outline dimensions	43.95(W) x72.00(H) x 7.50(D)	mm
Active area	36. 72 (W) *48. 96 (H)	mm
Resolution	240(H)RGBx320(V)	dots
Dot size	0.153(H) x 0.153(V)	mm

3 Module specification of the module



4 Electrical Characteristics

4.1 TFT-LCD Module

Parameter	Symbol	Condition	Specification			Unit	Related Pins
			MIN.	TYP.	MAX.		
Power & Operation Voltage							
System Voltage	VDD	Operating voltage	2.5	2.75	3.3	V	
Interface Operation Voltage	VDDI	I/O Supply Voltage	1.65	1.8	3.3	V	
Gate Driver High Voltage	VGH		10		15	V	
Gate Driver Low Voltage	VGL		-12.4		-7.5	V	
Gate Driver Supply Voltage		VGH-VGL	17.5		27.4	V	
Input / Output							
Logic-High Input Voltage	VIH		0.8VDDI		VDDI	V	Note 1
Logic-Low Input Voltage	VIL		VSS		0.2VDDI	V	Note 1
Logic-High Output Voltage	VOH	IOH = -1.0mA	0.8VDDI		VDDI	V	Note 1
Logic-Low Output Voltage	VOL	IOL = +1.0mA	VSS		0.2VDDI	V	Note 1
Logic-High Input Current	IIH	VIN = VDDI			1	uA	Note 1
Logic-Low Input Current	IIL	VIN = VSS	-1			uA	Note 1
Input Leakage Current	IIL	IOH = -1.0mA	-0.1		+0.1	uA	Note 1
VCOM Voltage							
VCOM amplitude	VCOM		-2		-0.425	V	
Source Driver							
Source Output Range	VSout		GVCL		GVDD	V	
Gamma Reference Voltage(Positive)	GVDD		3.15		4.7	V	
Gamma Reference Voltage(Negative)	GVCL		-4.7		-3.15	V	
Source Output Settling Time	Tr	Below with 99% precision			20	us	Note 2
Output Offset Voltage	VOFFSET				35	mV	Note 3

Table 2 Basic DC Characteristics

4.2 Back-Light Unit

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Current	IF	--	80	--	mA	IF=80mA IF=3.2V
Forward voltage	VF	3.0	3.2	3.4	V	
Chroma	X	0.250	--	0.30		
	Y	0.250	--	0.30		
Uniformity	UBL	80	--	--	%	
Number of LED	-	-	4	--	Piece	-
Backlight Color	White					

- The luminous intensity of LED is strongly dependent on the driving current.
- It is recommended the input of backlight to be constant current rather than constant voltage.

5 TFT-LCM Interface Specification

Pin No	Symbol	Description
1	GND	Ground
2	PWR	Backlight cathode
3	SCK	Serial clock signal
4	DC	Data/Command control Pin
5	3V3	Power supply
6	CS	LCD Chip select pin
7	SDA	Serial in signal
8	RST	Reset signal input

CON2	Symbol	Description
1	NC	No Connect
2	NC	No Connect
3	NC	No Connect
4	NC	No Connect
5	NC	No Connect
6	NC	No Connect
7	GND	Ground
8	GND	Ground
9	VCC	Power supply
10	VCC	Power supply
11	BL	Backlight cathode
12	DB15	Data Bit 15
13	DB14	Data Bit 14

深圳上线科技有限公司

Doc.No.:

REV: A

PAGE: 8/17

SPEC TITLE

DOCUMENT CONTROL SPECIFICATION

EFFECTIVE DATE: 2023-09-22

14	DB13	Data Bit 13
15	DB12	Data Bit 12
16	DB11	Data Bit 11
17	DB10	Data Bit 10
18	DB09	Data Bit 09
19	DB08	Data Bit 08
20	DB07	Data Bit 07
21	DB06	Data Bit 06
22	DB05	Data Bit 05
23	DB04	Data Bit 04
24	DB03	Data Bit 03
25	DB02	Data Bit 02
26	DB01	Data Bit 01
27	DB00	Data Bit 00
28	RESET	Reset signal input
29	RD	Read
30	WR	Write
31	RS	Register Select
32	CS	Chip Select

6 Timing Characteristics

Please refer to the ILI9341V specification.

7. Optical Specification

The optical characteristics are measured under stable conditions as following notes.

Table 3 Optical Characteristics

Item	Conditions		Min.	Typ.	Max.	Unit	Note
Viewing Angle (CR>10)	Horizontal	θ_{x+}	-	(45)	-	deg.	(1),(2),(6),(7), (8)
		θ_{x-}	-	(45)	-		
	Vertical	θ_{y+}	-	(45)	-		
		θ_{y-}	-	(20)	-		
Contrast Ratio	Center		-	(500)	-	-	(1),(3),(6),(7), (8)
Response Time	Rising + Falling		-	(20)	-	ms	(1),(4),(6),(7), (8)
CF Color Chromaticity (CIE1931)	Red	x		(0.626)		-	Under C-light
	Red	y		(0.334)		-	
	Green	x		(0.277)		-	
	Green	y	Typ.	(0.549)	Typ.	-	
	Blue	x	-0.03	(0.142)	+0.03	-	
	Blue	y		(0.122)		-	
	White	x		(0.303)		-	
	White	y		(0.325)		-	
NTSC	CIE1931		-	(60)	-	%	(1),(6),(7),(8)
Transmittance	Without POL		-	(15.7)	-	%	(1),(5),(6),(7), (8)


SPEC TITLE

DOCUMENT CONTROL SPECIFICATION

EFFECTIVE DATE: 2023-09-22

Note 1: The brightness test equipment setup


$I_B=60\text{mA}$, Field= 2° (As measuring “black” image, field= 2° is the best testing condition.)




Note 2: Definition of contrast ratio (C.R)

$$C.R = \frac{\text{Brightness When LCD is at “White” State}}{\text{Brightness When LCD is at “Black” State}}$$


Note 3: Definition of response time



Note 4: Definition of viewing angle



Note 5: Definition of uniformity (U_n)




$$U_n = \frac{B_{min}}{B_{max}} \times 100\%$$

8 Environment Absolute Maximum Ratings

Item	Symbol	Min	Max	Unit	Remark
Operation temperature range	Top	-20	70	°C	Ambient
Storage temperature range	Tst	-30	80	°C	Ambient

- Corrosive gas environment is not acceptable.
- TFT-LCD color will change slightly depending on environment temperature. This phenomenon is reversible. Current reduction rate of LED backlight is according to the graph indicated below:



Allowable Forward Current (mA)

9 Reliability Test Items


Item	Test Condition		Criterion	
High Temperature Storage	80 °C, 240 hrs		There should be no change which might affect the practical display function when the display quality test is conducted under normal operating condition.	
Low Temperature Storage	-30 °C, 240 hrs			
High Temp. & High Humidity Storage	60 °C, 90% RH, 240 hrs			
Vibration Test (Non-operating)	Freq.:10~55~10 Hz, Amp.:1.5mm 1 hr for each direction of X, Y, Z			
Electrostatic Discharge Test (Non-operating)	Terminals	150 pF, 0 Ω, ±300 V, Contact		
	Panel	150 pF, 330 Ω, ±8 KV, Air		
Thermal Shock (Static)	-30°C, 30 min /80°C, 30 min, 20 cycles			
High Temperature Operation	70 °C, 240 hrs			
Low temperature Operation	-20 °C, 240 hrs			
High Temperature & High Humidity (Operating)	50 °C, 90% RH, 240 hrs			
FPC Peeling Strength Test	Pull speed: 50 mm/min, +90°, > 400gf/cm			

10 Inspection Standard

This standard apply to TFT module specification.

1. Inspection condition:







Under daylight lamp 20~40W, product distance inspector'eye 30cm,incline degree 30° .



2. Inspection standard

NO.	Item	Inspection standard		Rate														
2.1	Dot	<p>Case of Dot defect is below</p> <ul style="list-style-type: none"> ① Bright Dot (whit spot) : "0" ② Dark Dot (black spot) : "0" (In case of Dark Dot on Main TFT LCD) <ul style="list-style-type: none"> - NG if there's full Dot defect. - Damaged less than the size of sub-pixel is not counted as defect. - Dots darker than the size of sub-pixel are not defined as bright dot defect 																
		<table border="1"> <thead> <tr> <th>area size (mm)</th> <th>Acceptable number</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.10$</td> <td>ignore</td> </tr> <tr> <td>$0.10 < \Phi \leq 0.15$</td> <td>3</td> </tr> <tr> <td>$0.15 < \Phi \leq 0.20$</td> <td>2</td> </tr> <tr> <td>$0.25 < \Phi \leq 0.25$</td> <td>1</td> </tr> <tr> <td>$0.25 < \Phi$</td> <td>0</td> </tr> </tbody> </table>	area size (mm)	Acceptable number	$\Phi \leq 0.10$	ignore	$0.10 < \Phi \leq 0.15$	3	$0.15 < \Phi \leq 0.20$	2	$0.25 < \Phi \leq 0.25$	1	$0.25 < \Phi$	0	minor			
area size (mm)	Acceptable number																	
$\Phi \leq 0.10$	ignore																	
$0.10 < \Phi \leq 0.15$	3																	
$0.15 < \Phi \leq 0.20$	2																	
$0.25 < \Phi \leq 0.25$	1																	
$0.25 < \Phi$	0																	
2.2	line	<table border="1"> <thead> <tr> <th colspan="2">Size (mm)</th> <th>Acceptable number</th> </tr> </thead> <tbody> <tr> <td>ignore</td> <td>$W \leq 0.03$</td> <td>ignore</td> </tr> <tr> <td>$L \leq 4.0$</td> <td>$0.03 < W \leq 0.04$</td> <td>2</td> </tr> <tr> <td>$L \leq 4.0$</td> <td>$0.04 < W \leq 0.05$</td> <td>1</td> </tr> <tr> <td></td> <td>$0.05 < W$</td> <td>Treat with dot non-conformance</td> </tr> </tbody> </table>	Size (mm)		Acceptable number	ignore	$W \leq 0.03$	ignore	$L \leq 4.0$	$0.03 < W \leq 0.04$	2	$L \leq 4.0$	$0.04 < W \leq 0.05$	1		$0.05 < W$	Treat with dot non-conformance	
Size (mm)		Acceptable number																
ignore	$W \leq 0.03$	ignore																
$L \leq 4.0$	$0.03 < W \leq 0.04$	2																
$L \leq 4.0$	$0.04 < W \leq 0.05$	1																
	$0.05 < W$	Treat with dot non-conformance																

11 Package

1		4	
	10 pcs per tray + 1 cover (EPE)		Packing bag
2		5	
	15 trays + 1 dummy tray = 150 ps		Putting bag into carton Protected by 2 pieces of cushion EPE sheet
3		6	
	Putting trays into anti-electrostatic bag		Packing carton with sealing tape Carton outline size: 400×295×145 (mm)

深圳上线科技有限公司	Doc.No.:	
	REV: A	PAGE: 15/17
SPEC TITLE DOCUMENT CONTROL SPECIFICATION	EFFECTIVE DATE: 2023-09-22	

12 Precautions

Please pay attentions to the followings as using the LCD module.

12.1 Handling

- (a) Do not apply strong mechanical stress like drop, shock or any force to LCD module. It may cause improper operation, even damage.
- (b) Because the polarizer is very fragile and easy to be damaged, do not hit, press or rub the display surface with hard materials.
- (c) Do not put heavy or hard material on the display surface, and do not stack LCD modules.
- (d) If the display surface is dirty, please wipe the surface softly with cotton swab or clean cloth.
- (e) Avoid using Ketone type materials (e.g. Acetone), Toluene, Ethyl acid or Methyl chloride to clean the display surface. It might damage the touch panel surface permanently. The recommended solvents are water and Isopropyl alcohol.
- (f) Wipe off water droplets or oil immediately.
- (g) Protect the LCD module from ESD. It will damage the LSI and the electronic circuit.
- (h) Do not touch the output pins directly with bare hands.
- (i) Do not disassemble the LCD module.
- (j) Do not lift the FPC of Touch Panel.

12.2 Storage

- (a) Do not leave the LCD modules in high temperature, especially in high humidity for a long time.
- (b) Do not expose the LCD modules to sunlight directly.
- (c) The liquid crystal is deteriorated by ultraviolet. Do not leave it in strong ultraviolet ray for a long time.
- (d) Avoid condensation of water. It may cause improper operation.


(e) Please stack only up to the number stated on carton box for storage and transportation. Excessive weight will cause deformation and damage of carton box.

12.3 Operation

- (a) When mounting or dismounting the LCD modules, turn the power off.
- (b) Protect the LCD modules from electric shock.
- (c) The Driver IC control algorithms stated above should always obeyed to avoid damaging the LSI and electronic circuit.
- (d) Be careful to avoid mixing up the polarity of power supply for backlight.
- (e) Absolute maximum rating specified above has to be always kept in any case. Exceeding it may cause non-recoverable damage of electronic components or, nevertheless, burning.
- (f) When a static image is displayed for a long time, remnant image is likely to occur.
- (g) Be sure to avoid bending the FPC to an acute shape, it might break FPC.
- (h) Most of the touch screens have air vent to equalize the inside air pressure to the outside one. The air vent must be open and liquid contact must be avoided as the liquid may be absorbed if the liquid is accumulated near the air vent.
- (i) For the fragility of ITO film, it should avoid to use too tapering pen as the input material.

12.4 Touch Panel Mounting Notes

- (a) If a cushion is used between bezel/housing and film must be choose as free as enough to absorb the expansion and contraction to avoid the distortion of film.
- (b) The cushion must be placed out of the Viewing Area.
- (c) Bezel/Housing edge must be posited between Key Area and Viewing Area. The edge enters the Key Area may cause unexpected input if the gap is too narrow or foreign particles like dusts exist between Bezel/Housing and ITO film.
- (d) Mounting example:



The corner part has conductivity. Do not touch any metal part after mounting.

12.5 Others

- If the liquid crystal leaks from the panel, it should be kept away from the eyes or mouth.
- For the fragility of polarizer, it is recommended to attach a transparent protective plate over the display surface.
- It is recommended to peel off the protection film on the polarizer slowly so that the electrostatic charge can be minimized.

13 Records of Version

Version	Revise Date	Page	Content
A	2023-09-22	All	New released