

ST7789V

ST7789V Application Note

**Ver 1.0
2013.10**

DISCLAIMER: THIS DOCUMENT IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. SITRONIX AND THE AUTHORS OF THIS DOCUMENT DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS DOCUMENT. THE PROVISION OF THIS DOCUMENT TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS

ST7789V

1	CMI Panel.....	5
1.1	CMI 2.4” Application FPC Circuit.....	5
1.2	CMI 2.4”Panel Initial code Suggestion.....	7
1.3	CMI 2.4” 2 Data Lane Serial I/F FPC Circuit.....	11
1.4	CMI 2.4” 2 Data Lane Serial I/F Initial code Suggestion.....	12
1.5	CMI 2.8” Application FPC Circuit.....	16
1.6	CMI 2.8”Panel Initial code Suggestion.....	18
2	CPT Panel.....	22
2.1	CPT 2.4” Application FPC Circuit.....	22
2.2	CPT 2.4” Panel Initial Code Suggestion.....	24
2.3	CPT 2.8” Application FPC Circuit.....	28
2.4	CPT 2.8”Panel Initial code Suggestion.....	30
3	Hannstar Panel.....	34
3.1	HANNS 2.4” Application FPC Circuit.....	34
3.2	HANNS 2.4”Panel Initial code Suggestion.....	36
3.3	HANNS 2.4” 2 Data Lane Serial I/F FPC Circuit.....	40
3.4	HANNS 2.4”Panel 2 Data Lane Initial code Suggestion.....	41
3.5	HANNS 2.6” Application FPC Circuit.....	45
3.6	HANNS 2.6”Panel Initial code Suggestion.....	47

ST7789V

3.7	HANNS 2.8" Application FPC Circuit.....	51
3.8	HANNS 2.8"Panel Initial code Suggestion.....	53
3.9	HANNS 3.2" Application FPC Circuit.....	57
3.10	HANNS 3.2"Panel Initial code Suggestion.....	59
4	BOE Panel	63
4.1	BOE 2.4"/2.8" Application FPC Circuit.....	63
4.2	BOE 2.4"Panel Initial code Suggestion.....	65
4.3	BOE 2.8"Panel Initial code Suggestion.....	69
5	TM Panel	73
5.1	TM 2.2" Application FPC Circuit.....	73
5.2	TM 2.2"Panel Initial code Suggestion.....	75
5.3	TM 2.4" Application FPC Circuit.....	79
5.4	TM 2.4"Panel Initial code Suggestion.....	81
5.5	TM 2.4" 2 Data Lane Serial I/F FPC Circuit.....	85
5.6	TM 2.4"Panel 2 Data Lane Initial code Suggestion	86
5.7	TM 2.8" Application FPC Circuit.....	90
5.8	TM 2.8"Panel Initial code Suggestion.....	92
5.9	TM 3.14" Application FPC Circuit.....	96
5.10	TM 3.14"Panel Initial code Suggestion.....	98

ST7789V

6	Laibao Panel	102
6.1	Laibao 2.0” Application FPC Circuit.....	102
6.2	Laibao 2.0”Panel Initial code Suggestion.....	104
7	Wintek Panel.....	108
7.1	Wintek 2.4” Application FPC Circuit.....	108
7.2	Wintek 2.4”Panel Initial code Suggestion	110
8	IVO Panel	114
8.1	IVO 2.4” Application FPC Circuit.....	114
8.2	IVO 2.4”Panel Initial code Suggestion.....	116
8.3	IVO 2.8” Application FPC Circuit.....	120
8.4	IVO 2.8”Panel Initial code Suggestion.....	122
9	History	126

ST7789V

1 CMI Panel





1.1 CMI 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. F02427-01U Product Spec_v1.1



- Note:
1. There is no CABG function in this schematic.
 2. Please connect input pins that are not used to VSS.

1.2 CMI 2.4" Panel Initial code Suggestion

```

Void ST7789VCMi24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x2b;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x11;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x05;
Write data 0x0e;
Write data 0x15;
Write data 0x0d;
Write data 0x37;
Write data 0x43;
Write data 0x47;
Write data 0x09;
Write data 0x15;
Write data 0x12;
Write data 0x16;
Write data 0x19;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x05;
Write data 0x0d;
Write data 0x0c;
Write data 0x06;
Write data 0x2d;
Write data 0x44;
Write data 0x40;
Write data 0x0e;
Write data 0x1c;
Write data 0x18;
Write data 0x16;
Write data 0x19;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;
```

Delaysms (120);

}

Void ST7789VPanelSleepOutMode (void)

{

Write command 0x11;

Delaysms (120);

}


1.3 CMI 2.4" 2 Data Lane Serial I/F FPC Circuit

2 Data Lane serial Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	1	0	1	3-line 9bit serial I/F	SDA: in/out, WRX: in

Panel Spec. Reference:

1. F02427-01U Product Spec_v1.1



1.4 CMI 2.4" 2 Data Lane Serial I/F Initial code Suggestion

```

Void ST7789VCMi24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x2b;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x11;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x05;
Write data 0x0e;
Write data 0x15;
Write data 0x0d;
Write data 0x37;
Write data 0x43;
Write data 0x47;
Write data 0x09;
Write data 0x15;
Write data 0x12;
Write data 0x16;
Write data 0x19;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x05;
Write data 0x0d;
Write data 0x0c;
Write data 0x06;
Write data 0x2d;
Write data 0x44;
Write data 0x40;
Write data 0x0e;
Write data 0x1c;
Write data 0x18;
Write data 0x16;
Write data 0x19;
Write command 0xe7;           //2 data lane interface enable
Write data 0x10;
```

```
Write command 0x29;
```

```
}
```

```
Void ST7789VPanelTurnOnDisplay (void)
```

```
{
```

```
Write command 0x29;
```

```
}
```

```
Void ST7789VPanelTurnOffDisplay (void)
```

```
{
```

```
Write command 0x28;
```

```
}
```

```
Void ST7789VPanelTurnOnPartial (void)
```

```
{
```

```
Write command 0x30;
```

```
Write data 0x00;
```

```
Write PSL;          //PSL: Start Line
```

```
Write data 0x00;
```

```
Write PEL;          //PEL: End Line
```

```
Write command 0x12;
```

```
}
```

```
Void ST7789VPanelTurnOffPartial (void)
```

```
{
```

```
Write command 0x13;
```

```
}
```

```
Void ST7789VPanelTurnOnIdle (void)
```

```
{
```

```
Write command 0x39;
```

```
}
```

```
Void ST7789VPanelTurnOffIdle (void)
```

```
{
```

```
Write command 0x38;
```

```
}
```

```
Void ST7789VPanelSleepInMode (void)
```

```
{  
Write command 0x10;  
Delays (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delays (120);  
}
```





1.5 CMI 2.8” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. F02812-01U TFT LCD Specification v1.5



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

1.6 CMI 2.8" Panel Initial code Suggestion

```
Void ST7789VCMi28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1); //Delay 1ms
LCD_RESET=0;
Delaysms(10); //Delay 10ms
LCD_RESET=1;
Delaysms(120); //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x28;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x01;
Write data 0x08;
Write data 0x0f;
Write data 0x11;
Write data 0x2a;
Write data 0x36;
Write data 0x55;
Write data 0x44;
Write data 0x3a;
Write data 0x0b;
Write data 0x06;
Write data 0x11;
Write data 0x20;
Write command 0xe1;
Write data 0xd0;
Write data 0x02;
Write data 0x07;
Write data 0x0a;
Write data 0x0b;
Write data 0x18;
Write data 0x34;
Write data 0x43;
Write data 0x4a;
Write data 0x2b;
Write data 0x1b;
Write data 0x1c;
Write data 0x22;
Write data 0x1f;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

2 CPT Panel





2.1 CPT 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. CLAF024G421 BX



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

2.2 CPT 2.4” Panel Initial Code Suggestion

```
Void ST7789VCPT24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//----- Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x1f;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x11;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x14;
Write data 0x15;
Write data 0x13;
Write data 0x2c;
Write data 0x42;
Write data 0x43;
Write data 0x4e;
Write data 0x09;
Write data 0x16;
Write data 0x14;
Write data 0x18;
Write data 0x21;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x14;
Write data 0x15;
Write data 0x13;
Write data 0x0b;
Write data 0x43;
Write data 0x55;
Write data 0x53;
Write data 0x0c;
Write data 0x17;
Write data 0x14;
Write data 0x23;
Write data 0x20;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delays (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delays (120);  
}
```





2.3 CPT 2.8” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. CLAF028GJ0100XA_Ver.0.2_2011.05.10



Note:

3. There is no CABC function in this schematic.
4. Please connect input pins that are not used to VSS

2.4 CPT 2.8" Panel Initial code Suggestion

```
Void ST7789VCPT28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1); //Delay 1ms
LCD_RESET=0;
Delaysms(10); //Delay 10ms
LCD_RESET=1;
Delaysms(120); //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x1f;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x17;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x14;
Write data 0x15;
Write data 0x13;
Write data 0x2c;
Write data 0x42;
Write data 0x43;
Write data 0x4e;
Write data 0x09;
Write data 0x16;
Write data 0x14;
Write data 0x18;
Write data 0x21;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x14;
Write data 0x15;
Write data 0x13;
Write data 0x0b;
Write data 0x43;
Write data 0x55;
Write data 0x53;
Write data 0x0c;
Write data 0x17;
Write data 0x14;
Write data 0x23;
Write data 0x20;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

3 Hannstar Panel





3.1 HANNS 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. HSD024F3N5-A Preliminary Specification 1.0(14umIC)



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

3.2 HANNS 2.4”Panel Initial code Suggestion

```
Void ST7789VHANNS24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1); //Delay 1ms
LCD_RESET=0;
Delaysms(10); //Delay 10ms
LCD_RESET=1;
Delaysms(120); //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x35;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0b;
Write data 0x1a;
Write data 0x31;
Write data 0x54;
Write data 0x40;
Write data 0x29;
Write data 0x12;
Write data 0x12;
Write data 0x12;
Write data 0x17;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x05;
Write data 0x25;
Write data 0x2d;
Write data 0x44;
Write data 0x45;
Write data 0x1c;
Write data 0x18;
Write data 0x16;
Write data 0x1c;
Write data 0x1d;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```


3.4 HANNS 2.4"Panel 2 Data Lane Initial code Suggestion

```

Void ST7789VHANNS24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x35;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0b;
Write data 0x1a;
Write data 0x31;
Write data 0x54;
Write data 0x40;
Write data 0x29;
Write data 0x12;
Write data 0x12;
Write data 0x12;
Write data 0x17;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x05;
Write data 0x25;
Write data 0x2d;
Write data 0x44;
Write data 0x45;
Write data 0x1c;
Write data 0x18;
Write data 0x16;
Write data 0x1c;
Write data 0x1d;
Write command 0xe7; //2 data lane interface enable
Write data 0x10;
```

```
Write command 0x29;  
}
```

```
Void ST7789VPanelTurnOnDisplay (void)  
{  
Write command 0x29;  
}
```

```
Void ST7789VPanelTurnOffDisplay (void)  
{  
Write command 0x28;  
}
```

```
Void ST7789VPanelTurnOnPartial (void)  
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

```
Void ST7789VPanelTurnOffPartial (void)  
{  
Write command 0x13;  
}
```

```
Void ST7789VPanelTurnOnIdle (void)  
{  
Write command 0x39;  
}
```

```
Void ST7789VPanelTurnOffIdle (void)  
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;  
Delaysms (120);  
}
```

Void ST7789VPanelSleepOutMode (void)

```
{  
Write command 0x11;  
Delaysms (120);  
}
```





3.5 HANNS 2.6” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. HSD026B3N3-B



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

3.6 HANNS 2.6" Panel Initial code Suggestion

```
Void ST7789VHANNS26panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x35;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0b;
Write data 0x1a;
Write data 0x31;
Write data 0x54;
Write data 0x40;
Write data 0x29;
Write data 0x12;
Write data 0x12;
Write data 0x12;
Write data 0x17;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x05;
Write data 0x25;
Write data 0x2d;
Write data 0x44;
Write data 0x45;
Write data 0x1c;
Write data 0x18;
Write data 0x16;
Write data 0x1c;
Write data 0x1d;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delays (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delays (120);  
}
```

3.7 HANNS 2.8” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. HSD028B3N1-A Formal Specification For Truly

3.8 HANNS 2.8" Panel Initial code Suggestion

```

Void ST7789VHANNS28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x28;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x10;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0a;
Write data 0x28;
Write data 0x32;
Write data 0x44;
Write data 0x42;
Write data 0x06;
Write data 0x0e;
Write data 0x12;
Write data 0x14;
Write data 0x17;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0a;
Write data 0x28;
Write data 0x31;
Write data 0x54;
Write data 0x47;
Write data 0x0e;
Write data 0x1c;
Write data 0x17;
Write data 0x1b;
Write data 0x1e;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delays (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delays (120);  
}
```

3.9 HANNS 3.2” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. HSD032B3N5-A02

3.10 HANNS 3.2"Panel Initial code Suggestion

```

Void ST7789VHANNS32panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1);                //Delay 1ms
LCD_RESET=0;
Delaysms(10);               //Delay 10ms
LCD_RESET=1;
Delaysms(120);              //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120);              //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x28;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x10;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0a;
Write data 0x28;
Write data 0x32;
Write data 0x44;
Write data 0x42;
Write data 0x06;
Write data 0x0e;
Write data 0x12;
Write data 0x14;
Write data 0x17;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x02;
Write data 0x07;
Write data 0x0a;
Write data 0x28;
Write data 0x31;
Write data 0x54;
Write data 0x47;
Write data 0x0e;
Write data 0x1c;
Write data 0x17;
Write data 0x1b;
Write data 0x1e;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

4 BOE Panel

4.1 BOE 2.4"/2.8" Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. 2.4QVGA PRODUCT SPEC BT024QVME104 (Cell)(NEW)
2. 五代线 BT028QVME101-D001 2.8QVGA PS B1 Cell

4.2 BOE 2.4" Panel Initial code Suggestion

```

Void ST7789VBOE24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1); //Delay 1ms
LCD_RESET=0;
Delaysms(10); //Delay 10ms
LCD_RESET=1;
Delaysms(120); //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x1c;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x09;
Write data 0x13;
Write data 0x1c;
Write data 0x3a;
Write data 0x55;
Write data 0x48;
Write data 0x18;
Write data 0x12;
Write data 0x0e;
Write data 0x19;
Write data 0x1e;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x09;
Write data 0x05;
Write data 0x25;
Write data 0x3a;
Write data 0x55;
Write data 0x50;
Write data 0x3d;
Write data 0x1c;
Write data 0x1d;
Write data 0x1d;
Write data 0x1e;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

4.3 BOE 2.8" Panel Initial code Suggestion

```
Void ST7789VBOE28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delaysms(1); //Delay 1ms
LCD_RESET=0;
Delaysms(10); //Delay 10ms
LCD_RESET=1;
Delaysms(120); //Delay 120ms
//-----//
Write command 0x11;
Delaysms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x20;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x03;
Write data 0x09;
Write data 0x0e;
Write data 0x11;
Write data 0x3d;
Write data 0x47;
Write data 0x55;
Write data 0x53;
Write data 0x1a;
Write data 0x16;
Write data 0x14;
Write data 0x1f;
Write data 0x22;
Write command 0xe1;
Write data 0xd0;
Write data 0x02;
Write data 0x08;
Write data 0x0d;
Write data 0x12;
Write data 0x2c;
Write data 0x43;
Write data 0x55;
Write data 0x53;
Write data 0x1e;
Write data 0x1b;
Write data 0x19;
Write data 0x20;
Write data 0x22;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;
```

```
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

5 TM Panel





5.1 TM 2.2” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. TM022HYH31 32 33 34_V1 1 Approving



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

5.2 TM 2.2”Panel Initial code Suggestion

```

Void ST7789VTM22panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x20;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x0a;
Write data 0x17;
Write data 0x2e;
Write data 0x44;
Write data 0x3f;
Write data 0x29;
Write data 0x10;
Write data 0x0e;
Write data 0x14;
Write data 0x18;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x07;
Write data 0x27;
Write data 0x2b;
Write data 0x44;
Write data 0x41;
Write data 0x3c;
Write data 0x1b;
Write data 0x1d;
Write data 0x14;
Write data 0x18;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

Write command 0x10;

Delaysms (120);

}

Void ST7789VPanelSleepOutMode (void)

{

Write command 0x11;

Delaysms (120);

}

5.3 TM 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. TM024HYH61&62_V1.0.Final Specification

5.4 TM 2.4”Panel Initial code Suggestion

```

Void ST7789VTM24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x20;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x0a;
Write data 0x17;
Write data 0x2e;
Write data 0x44;
Write data 0x3f;
Write data 0x29;
Write data 0x10;
Write data 0x0e;
Write data 0x14;
Write data 0x18;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x07;
Write data 0x27;
Write data 0x2b;
Write data 0x44;
Write data 0x41;
Write data 0x3c;
Write data 0x1b;
Write data 0x1d;
Write data 0x14;
Write data 0x18;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```

```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```


5.5 TM 2.4" 2 Data Lane Serial I/F FPC Circuit

2 Data Lane Serial Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	1	0	1	3-line 9bit serial I/F	SDA: in/out, WRX: in

Panel Spec. Reference:

0. TM024HYH61&62_V1.0.Final Specification



5.6 TM 2.4”Panel 2 Data Lane Initial code Suggestion

```

Void ST7789VTM24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x20;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x0a;
Write data 0x17;
Write data 0x2e;
Write data 0x44;
Write data 0x3f;
Write data 0x29;
Write data 0x10;
Write data 0x0e;
Write data 0x14;
Write data 0x18;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x03;
Write data 0x08;
Write data 0x07;
Write data 0x27;
Write data 0x2b;
Write data 0x44;
Write data 0x41;
Write data 0x3c;
Write data 0x1b;
Write data 0x1d;
Write data 0x14;
Write data 0x18;
Write command 0xe7;           //2 data lane interface enable
Write data 0x10;
```

```
Write command 0x29;  
}
```

```
Void ST7789VPanelTurnOnDisplay (void)  
{  
Write command 0x29;  
}
```

```
Void ST7789VPanelTurnOffDisplay (void)  
{  
Write command 0x28;  
}
```

```
Void ST7789VPanelTurnOnPartial (void)  
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

```
Void ST7789VPanelTurnOffPartial (void)  
{  
Write command 0x13;  
}
```

```
Void ST7789VPanelTurnOnIdle (void)  
{  
Write command 0x39;  
}
```

```
Void ST7789VPanelTurnOffIdle (void)  
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;  
Delaysms (120);  
}
```

Void ST7789VPanelSleepOutMode (void)

```
{  
Write command 0x11;  
Delaysms (120);  
}
```

5.7 TM 2.8” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. TM028HYS01_V1.0

5.8 TM 2.8" Panel Initial code Suggestion

```
Void ST7789VTM28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x15;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;
```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x09;
Write data 0x0c;
Write data 0x0e;
Write data 0x28;
Write data 0x31;
Write data 0x43;
Write data 0x42;
Write data 0x3a;
Write data 0x14;
Write data 0x15;
Write data 0x15;
Write data 0x1a;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x09;
Write data 0x0c;
Write data 0x0c;
Write data 0x28;
Write data 0x2d;
Write data 0x45;
Write data 0x41;
Write data 0x3b;
Write data 0x19;
Write data 0x16;
Write data 0x15;
Write data 0x1b;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

Write command 0x10;

Delaysms (120);

}

Void ST7789VPanelSleepOutMode (void)

{

Write command 0x11;

Delaysms (120);

}





5.9 TM 3.14” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. TM031HYS21&TM031HYS22_V1.0.Preliminary Specification



Note:

1. There is no CABC function in this schematic.
2. Please connect input pins that are not used to VSS

5.10 TM 3.14”Panel Initial code Suggestion

```

Void ST7789VTM314panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x15;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x0b;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x04;
Write data 0x0a;
Write data 0x0b;
Write data 0x28;
Write data 0x2f;
Write data 0x54;
Write data 0x42;
Write data 0x09;
Write data 0x14;
Write data 0x14;
Write data 0x17;
Write data 0x1c;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x04;
Write data 0x0a;
Write data 0x0b;
Write data 0x27;
Write data 0x2f;
Write data 0x44;
Write data 0x43;
Write data 0x0b;
Write data 0x15;
Write data 0x15;
Write data 0x18;
Write data 0x1d;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

Write command 0x10;

Delaysms (120);

}

Void ST7789VPanelSleepOutMode (void)

{

Write command 0x11;

Delaysms (120);

}

6 Laibao Panel





6.1 Laibao 2.0” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. LaibaoS20008F112G46S2T5-LCD-Ver02(2.0QVGANew)



Note:

1. There is no CABG function in this schematic.
2. Please connect input pins that are not used to VSS

6.2 Laibao 2.0"Panel Initial code Suggestion

```

Void ST7789VLaibao20panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display and color format setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35;
//-----ST7789V Power setting-----//
Write command 0xbb;
Write data 0x35;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x11;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----ST7789V gamma setting-----//
Write command 0xe0;
Write data 0xd0;
Write data 0x00;
Write data 0x06;
Write data 0x09;
Write data 0x0b;
Write data 0x2a;
Write data 0x3c;
Write data 0x55;
Write data 0x4b;
Write data 0x08;
Write data 0x16;
Write data 0x14;
Write data 0x19;
Write data 0x20;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x06;
Write data 0x09;
Write data 0x0b;
Write data 0x29;
Write data 0x36;
Write data 0x54;
Write data 0x4b;
Write data 0x0d;
Write data 0x16;
Write data 0x14;
Write data 0x21;
Write data 0x20;
Write command 0x29;
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{
```

```
Write command 0x10;  
Delaysms (120);  
}
```





```
Void ST7789VPanelSleepOutMode (void)  
{  
Write command 0x11;  
Delaysms (120);  
}
```

7 Wintek Panel

7.1 Wintek 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out



Note:

3. There is no CABG function in this schematic.
4. Please connect input pins that are not used to VSS

7.2 Wintek 2.4"Panel Initial code Suggestion

```

Void ST7789Vwintek24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35; //VGH=13V, VGL=-10.4V
//-----//
Write command 0xbb;
Write data 0x19;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x05;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----//
Write command 0xe0;           //gamma setting
Write data 0xd0;
Write data 0x00;
Write data 0x00;
Write data 0x0a;
Write data 0x0b;
Write data 0x28;
Write data 0x30;
Write data 0x54;
Write data 0x42;
Write data 0x1a;
Write data 0x16;
Write data 0x15;
Write data 0x16;
Write data 0x1b;
Write command 0xe1;
Write data 0xd0;
Write data 0x00;
Write data 0x00;
Write data 0x0a;
Write data 0x0a;
Write data 0x28;
Write data 0x2d;
Write data 0x44;
Write data 0x42;
Write data 0x1b;
Write data 0x16;
Write data 0x16;
Write data 0x17;
Write data 0x1a;
Write command 0x29;           //display on
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;
```

```
Delaysms (120);
```

```
}
```

```
Void ST7789VPanelSleepOutMode (void)
```

```
{
```

```
Write command 0x11;
```

```
Delaysms (120);
```

```
}
```

8 IVO Panel





8.1 IVO 2.4” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. C024SW21 Product Specification



Note:

- There is no CABC function in this schematic.
- Please connect input pins that are not used to VSS

8.2 IVO 2.4" Panel Initial code Suggestion

```

Void ST7789VIVO24panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35; //VGH=13V, VGL=-10.4V
//-----//
Write command 0xbb;
Write data 0x19;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x12;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----//
Write command 0xe0;           //gamma setting
Write data 0xd0;
Write data 0x04;
Write data 0x0d;
Write data 0x11;
Write data 0x13;
Write data 0x2b;
Write data 0x3f;
Write data 0x54;
Write data 0x4c;
Write data 0x18;
Write data 0x0d;
Write data 0x0b;
Write data 0x1f;
Write data 0x23;
Write command 0xe1;
Write data 0xd0;
Write data 0x04;
Write data 0x0c;
Write data 0x11;
Write data 0x13;
Write data 0x2c;
Write data 0x3f;
Write data 0x44;
Write data 0x51;
Write data 0x2f;
Write data 0x1f;
Write data 0x1f;
Write data 0x20;
Write data 0x23;
Write command 0x29;           //display on
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;
```

```
Delaysms (120);
```

```
}
```

```
Void ST7789VPanelSleepOutMode (void)
```

```
{
```

```
Write command 0x11;
```

```
Delaysms (120);
```

```
}
```

8.3 IVO 2.8” Application FPC Circuit

ST7789V Interface Selection:

IM3	IM2	IM1	IM0	MPU Interface Mode	Data pin
0	0	0	0	80-8bit parallel I/F	DB[7:0]
0	0	0	1	80-16bit parallel I/F	DB[15:0]
0	0	1	0	80-9bit parallel I/F	DB[8:0]
0	0	1	1	80-18bit parallel I/F	DB[17:0],
0	1	0	1	3-line 9bit serial I/F	SDA: in/out
0	1	1	0	4-line 8bit serial I/F	SDA: in/out
1	0	0	0	80-16bit parallel I/F II	DB[17:10], DB[8:1]
1	0	0	1	80-8bit parallel I/F II	DB[17:10]
1	0	1	0	80-18bit parallel I/F II	DB[17:0],
1	0	1	1	80-9bit parallel I/F II	DB[17:9]
1	1	0	1	3-line 9bit serial I/F II	SDA:in/ SDO: out
1	1	1	0	4-line 8bit serial I/F II	SDA:in/ SDO: out

Panel Spec. Reference:

1. C028SN21-0 Product Specification

8.4 IVO 2.8" Panel Initial code Suggestion

```

Void ST7789VIVO28panelinitialcode(void)
{
//-----ST7789V reset sequence-----//
LCD_RESET=1;
Delayms(1); //Delay 1ms
LCD_RESET=0;
Delayms(10); //Delay 10ms
LCD_RESET=1;
Delayms(120); //Delay 120ms
//-----//
Write command 0x11;
Delayms(120); //Delay 120ms
//-----Display Setting-----//
Write command 0x36;
Write data 0x00;
Write command 0x3a;
Write data 0x06;
//-----ST7789V Frame rate setting-----//
Write command 0xb2;
Write data 0x0c;
Write data 0x0c;
Write data 0x00;
Write data 0x33;
Write data 0x33;
Write command 0xb7;
Write data 0x35; //VGH=13V, VGL=-10.4V
//-----//
Write command 0xbb;
Write data 0x19;
Write command 0xc0;
Write data 0x2c;
Write command 0xc2;
Write data 0x01;
Write command 0xc3;
Write data 0x12;
Write command 0xc4;

```

```
Write data 0x20;
Write command 0xc6;
Write data 0x0f;
Write command 0xd0;
Write data 0xa4;
Write data 0xa1;
//-----//
Write command 0xe0;                //gamma setting
Write data 0xd0;
Write data 0x04;
Write data 0x0d;
Write data 0x11;
Write data 0x13;
Write data 0x2b;
Write data 0x3f;
Write data 0x54;
Write data 0x4c;
Write data 0x18;
Write data 0x0d;
Write data 0x0b;
Write data 0x1f;
Write data 0x23;
Write command 0xe1;
Write data 0xd0;
Write data 0x04;
Write data 0x0c;
Write data 0x11;
Write data 0x13;
Write data 0x2c;
Write data 0x3f;
Write data 0x44;
Write data 0x51;
Write data 0x2f;
Write data 0x1f;
Write data 0x1f;
Write data 0x20;
Write data 0x23;
Write command 0x29;                //display on
}
```

Void ST7789VPanelTurnOnDisplay (void)

```
{  
Write command 0x29;  
}
```

Void ST7789VPanelTurnOffDisplay (void)

```
{  
Write command 0x28;  
}
```

Void ST7789VPanelTurnOnPartial (void)

```
{  
Write command 0x30;  
Write data 0x00;  
Write PSL;          //PSL: Start Line  
Write data 0x00;  
Write PEL;          //PEL: End Line  
Write command 0x12;  
}
```

Void ST7789VPanelTurnOffPartial (void)

```
{  
Write command 0x13;  
}
```

Void ST7789VPanelTurnOnIdle (void)

```
{  
Write command 0x39;  
}
```

Void ST7789VPanelTurnOffIdle (void)

```
{  
Write command 0x38;  
}
```

Void ST7789VPanelSleepInMode (void)

```
{  
Write command 0x10;
```

```
Delaysms (120);
```

```
}
```

```
Void ST7789VPanelSleepOutMode (void)
```

```
{
```

```
Write command 0x11;
```

```
Delaysms (120);
```

```
}
```

9 History

ST7789V Application Note Revision History		
Version	Date	Description
1.0	2013/10	First issue